

Алматы (7273)495-231	Ижевск (3412)26-03-58	Магнитогорск (4219)55-03-13	Пермь (342)205-81-47	Тверь (4352)63-31-42
Ангарск (3955)42-70-56	Иваново (4932)77-34-06	Москва (495)268-04-70	Ростов-на-Дону (863)308-18-15	Тольятти (8435)63-91-07
Архангельск (8182)63-90-72	Иркутск (395)279-98-46	Мурманск (8152)59-142-93	Рязань (4912)46-61-142	Томск (3835)98-41-53
Астрахань (8512)99-46-04	Казань (843)206-01-42	Набережные Челны (8552)20-53-41	Самара (846)206-03-16	Тула (4272)33-79-87
Барнаул (3852)73-04-42	Калининград (4012)72-03-81	Нижний Новгород (831)429-08-12	Саранск (8342)35-96-24	Тюмень (3452)66-21-18
Белгород (4735)40-23-142	Калуга (4242)92-23-67	Новокузнецк (3843)20-46-81	Санкт-Петербург (812)309-46-40	Улан-Удэ (3012)59-97-51
Благовещенск (4162)35-142-07	Кемерово (3842)65-04-62	Ноябрьск (3496)41-32-12	Саратов (845)249-38-78	Ульяновск (8435)24-23-59
Брянск (4232)59-03-52	Киров (8332)68-02-04	Новосибирск (383)357-86-73	Севастополь (8692)35-31-93	Уфа (347)359-42-12
Владивосток (423)249-42-31	Коломна (4966)23-41-49	Ноябрьск (3496)41-32-12	Симферополь (3652)67-13-56	Хабаровск (4212)92-98-04
Владикавказ (8672)42-90-42	Кострома (4942)77-07-42	Омск (3812)21-46-40	Смоленск (4212)29-41-42	Чебоксары (8435)42-53-07
Владимир (4935) 49-43-18	Краснодар (861)203-40-90	Орел (4262)44-53-42	Сочи (862)242-72-31	Челябинск (421)202-03-61
Волгоград (844)278-03-42	Красноярск (391)204-63-61	Оренбург (4232)37-68-04	Ставрополь (8652)20-65-13	Череповец (8202)49-02-142
Вологда (8172)26-41-59	Курск (4712)77-13-04	Пенза (8412)35-31-16	Сыктывкар (8212)42-95-17	Чита (3035)38-34-83
Воронеж (473)204-51-73	Курган (4352)50-90-47	Петрозаводск (8142)55-98-37	Сургут (3462)77-98-42	Якутск (4112)23-90-97
Екатеринбург (343)384-55-142	Липецк (4742)52-20-81	Псков (8112)59-10-37	Тамбов (4752)50-40-97	Ярославль (4422)69-52-93
Киргизия (996)312-96-26-47		Россия (495)268-04-70		Казахстан (772)734-952-31

<https://cadoppi.nt-rt.ru> || cip@nt-rt.ru

Погружные дренажные и отстойные насосы XD.

Технические характеристики

Cadoppi XD series stainless steel submersible drainage and sump pumps are designed for sump drainage, drainage, gray water and pure water applications. These pumps are equipped with a stainless steel semi-open impeller capable of passing 8 mm solids.

Pump characteristics / Caractéristiques de la pompe

Technical data / Données Techniques		
Conditions of use Conditions d'utilisation	Applications	Underground water pumping, Drainage of waste water, Wastewater treatment Pompage d'eau sous-sol, Drainage des eaux usées, Assèchement, Traitement des eaux usées
	Fluid temp. / Temp. du fluide max	50 °C
Motor / Moteur	Pole / Pôle	2
	Speed max / Vitesse max	2900 rpm
	Power / Puissance max	0.55 ÷ 1.5kW
	Power supply / Alimentation	220/240 V ~1 – 380/400 V ~3
	Insulation / Isolation	F Class / Classe F
Pump / Pompe	Protection / Protection	IP 68
	Rated Flow / Debit max	27 m³/h
	Max Heads / Hmt max	21 m
	Impeller type / Type de roue	
	Free passage / Passage solide	8 mm
	Discharge size / Refoulement	RP 1 1/2"



Pump materials / Matériaux de la pompe

Components / Composants	Materials / Matériaux
Câble / Câble	H07 RNF
Handle / Poignée	AISI 304 + Nylon
Motor cover / Couverture du moteur	AISI 304
Motor body / Boîtier du moteur	AISI 304
Fixing ring / Anneau de fixation	AISI 304
Pump body / Corps de pompe	AISI 304
Mechanical seal / Garniture mécanique	SIC/SIC/NBR / SIC/SIC/NBR
Impeller / Turbine	AISI 304
Suction flange / Bride d'aspiration	AISI 304
Pump cage / Boîtier de pompe	AISI 304
Seal joint / Joint d'étanchéité	NBR / NBR
Gasket / Garniture	AISI 304

Characteristic curve / Courbe caractéristiques

