

Алматы (7273)495-231
Ангарск (3955)42-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-42
Белгород (4735)40-23-142
Благовещенск (4162)35-142-07
Брянск (4232)59-03-52
Владивосток (423)249-42-31
Владикавказ (8672)42-90-42
Владимир (4935) 49-43-18
Волгоград (844)278-03-42
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-142

Ижевск (3412)26-03-58
Иваново (4932)77-34-06
Иркутск (395)279-98-46
Казань (843)206-01-42
Калининград (4012)72-03-81
Калуга (4242)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-42
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (4352)50-90-47
Липецк (4742)52-20-81

Киргизия (996)312-96-26-47

Магнитогорск (4219)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-142-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)357-86-73
Ноябрьск (3496)41-32-12
Омск (3812)21-46-40
Орел (4262)44-53-42
Оренбург (4232)37-68-04
Пенза (8412)35-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37

Россия (495)268-04-70

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-142
Самара (846)206-61-16
Саранск (8342)35-96-24
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)35-31-93
Симферополь (3652)67-13-56
Смоленск (4212)29-41-42
Сочи (862)242-72-31
Ставрополь (8652)20-65-13
Сыктывкар (8212)42-95-17
Сургут (3462)77-98-42
Тамбов (4752)50-40-97

Казахстан (772)734-952-31

Тверь (4352)63-31-42
Тольятти (8435)63-91-07
Томск (3835)98-41-53
Тула (4272)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Ульяновск (8435)24-23-59
Уфа (347)359-42-12
Хабаровск (4212)92-98-04
Чебоксары (8435)42-53-07
Челябинск (421)202-03-61
Череповец (8202)49-02-142
Чита (3035)38-34-83
Якутск (4112)23-90-97
Ярославль (4422)69-52-93

<https://cadoppi.nt-rt.ru> || cip@nt-rt.ru

Пожарный насос D-FIGHTER.

Технические характеристики

Our comprehensive range of fire protection solutions includes:
Electric and diesel fire pumps in horizontal configuration, split-case pumps,
pumps in vertical configuration.

Available as single pump units or complete systems with or without cabin

Control box

Main Features

- Execution of the standards and technical rules in force:
- Battery charger SCQB
- Norme : NF-EN 12845 Edition 2005+A2:2010
- Norme : UNE 23500 Edition 2012
- Charging curve adapted to the battery
- Flotation charge
- Charger signal OK
- Charge inhibition for a more correct measurement of the battery condition
- Measuring instruments:
 - 2 Battery voltage voltmeters
 - 2 Ammeters of battery charging current
- Fuel level
- Refrigerant temperature
- Oil pressure
- Engine speed in rpm
- Other information offered in the display
- Date et heure actuelles
- History of 47 recorded events
- Accumulated hours of engine operation
- 15 Pump and system alarms
- Other Character
- Engine heating management by reading the temperature
- Fuel movement pump management (optional)
- Automated weekly or monthly periodic test process (optional)
- Start of the motor pump by external command (optional)
- Starting the refrigeration circuit

